

PERFORMANCE COLLECTION

Click Lock Luxury Vinyl Plank



Specifications

Physical Construction

COMPOSITION:	StoneTec™/SCC (Stone Composite Core)
CONSTRUCTION:	Click Lock
WEAR LAYER THICKNESS:	12 Mil
OVERALL THICKNESS:	4.5mm (3.5mm+1mm EVA Pad)
FINISH:	Aluminum Oxide
EDGE PROFILE:	Painted Bevel
ANTIMICROBIAL TREATMENT:	Yes
INSTALLATION:	Floating / Intermediate Level
LOCKING SYSTEM:	Unilin
RECOMMENDED ADHESIVE:	None Required
MEASUREMENTS:	7"x48" 10 planks per carton/23.64 sq ft per carton 70 cartons per pallet/1,654.8 sq ft per pallet
WARRANTY:	5-Year Limited Light Commercial Wear 15-Year Limited Residential Wear
ADDITIONAL BENEFITS:	100% Waterproof, Floor Score Certified, Antimicrobial, Scratch & Slip-Resistant



CLICK



StoneTec™



CERTIFIED BY
SCS Global Services



RESIDENTIAL



COMMERCIAL

NOTE: Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.